

New Generation of TODO-MATIC® Hose Unit

The latest model of the 3" hose unit (43xx-xxxx) from TODO has turned out to be a success since it was released. The unit offers advanced design and performance features not previously achievable and are available in both TODO-MATIC® and TODO-GAS® variants.

The hose unit is fully interchangeable with all previous and current TODO-MATIC® and TODO-GAS® tank units as well as products conforming to the N.A.T.O. standard STANAG 3756 dimensional specifications.

The hose unit offers the following features and benefits

- Improved ease of connection against pressure.
- New twin ball race swivel offers increased strength and reduced torque force in operation.
- A reduction from four to two elastomeric seals offers cost and maintenance savings, particularly when using High Specification Perfluoroelastomer (FFKM) seals.
- Reduced residual liquid on disconnection.
- Fully connected locking facility eliminates unintentional disconnection when subjected to vibration from transfer pumps.

The hose unit from TODO® is available in stainless steel 316L with a full complement of flange / threaded connections and choice of elastomeric seals.



*3" TODO-MATIC® Dry-Break coupling
hose unit in Stainless Steel*

*Better by
Design*

TODO[®]
A Gardner Denver Product

TODO AB

Box 33 · 545 21 Töreboda, SWEDEN
Tel +46 (0)506 199 40 · Fax +46 (0)506 199 44
assist@todo.se · www.todo.se